FLOWITA EVO



Wall-mounted monobloc pump, dismountable, for the condensate removal from air conditioners up to 10kW / 36000BTU.

Ref: DE05LCC440







ECO







SPECIFICATIONS

| Flowrate max | 13.2 l/h |
|--------------------|---------------------|
| Discharge head max | 10 m |
| Electrical power | 19W |
| Voltage | 220-240V 50/60Hz |
| Alarm | No alarm |
| Noise level | \triangleleft |
| Protection rating | IP24 |
| Thermal protection | Yes |
| Operating cycle* | 100% |
| Power cable | 0.8 m |
| Tank capacity | 170 ml |
| Dimensions | 135 x 57 x 106.5 mm |
| Certifications | CE, EAC |


^{*} The pump is able to run 100% of the time if necessary.





Hose diameter
Discharge: 6/9 mm - not supplied

BENEFITS



Dismountable |

The FLOWITA EVO can be disassembled in seconds!

Front panel, tank, suction tube... all the elements are removable.

Installation and maintenance has never been so quick and easy!



170ml reservoir

Its large reservoir allows the pump to operate optimally: larger and less frequent pumping cycles.



Very silent

One of the most discreet wall-mounted pump on the market!



Quick installation

The FLOWITA EVO can be installed easily and quickly underneath any air conditioner.



IP24 protection

Protected against water splashes.

CONTENTS

Pump - Screws and rawlplugs

